



Ultra•Strip III Hang Tag (Bag)

The Ultra•Strip III Hang Tag provides premier protection for accessory items such as costume jewelry, watches and sunglasses. The tag attaches to merchandise via a plastic or string lanyard supplied by the retailer or manufacturer. It can be used once or multiple times. The tag format is intended for source tagging accessory items.

Retailer Values

- // Designed to protect high-theft accessories
- // Utilizes proven Sensormatic AM technology and manufacturing process to provide the highest in detection performance
- // Small label footprint minimizes impact on brand promotion and important product information
- // Reactivable for unlimited reuse
- // Works well on liquids, foils and in metal shopping carts
- // Robust construction provides optimal merchandise protection

Product Codes

ZLDRHT1

Technology

AM

Environmental Constraints

Temperature

Maximum storage temperature not to exceed 50°C (122°F) for 96 hours at 80% RH.

Humidity

Unaffected by 80% humidity at 50°C (122°F), up to 96 hours.

Shelf Life

Two years from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 30-80% RH.

Product Compatibility

Sensormatic AM detection and deactivation devices.

Mode of Application

Hand

Materials of Construction

Plastic Substrate

Polystyrene/Polyethylene 0.3mm (0.012in) thick magnetic.

Magnetic Acoustic Resonator

Resonant magnetic material. Amorphous alloy based on iron, containing nickel, cobalt, boron and silicon

Laminate

Low Density Polyethylene/Polyester/Polyethylene 0.127mm (0.0050in)

Bias

Proprietary semi-hard magnetic material containing iron, nickel and chromium

Adhesive

Adhesive=Acrylic. Facestock=80 pound densified bleached Kraft, silicone coated one side

Dimensions

Color White

Length.....58mm ± 0.5mm
(2.28in ± 0.020in)

Width 10mm ± 0.5mm
(0.394in ± 0.020in)

Label Thickness
(including liner)..... Maximum
2.0mm (0.078in)

Labels Per Bag 100

Note: Warranty terms and conditions are as specified in the applicable Sales Agreement.

CE The acousto-magnetic (AM) label is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

See Sensormatic.com for Usage Instructions

BAG SPECS	
	Label Tag
PRODUCT CODE	ZLDRHT1
Case Weight	0.86kg (1.90lbs)
External Carton Dimensions	27.9 x 20 x 11cm (11 x 8 x 4.5in)
External Cubic Ft. Per Case	0.23
Cases Per Pallet	140
Order Multiple	1,000-unit case (10 bags of 100 labels each)