



## Ultra•Strip III Low Profile Roll Label

The Ultra•Strip III Low Profile Label provides premier performance and protection for CDs, DVDs and other slim merchandise. Designed for automatic application.

### Retailer Values

- // Protects CDs, DVDs and other applications with height restrictions
- // Utilizes proven Sensormatic AM technology and manufacturing process to provide the highest in detection performance
- // Small label footprint minimizes impact on brand promotion and important product information
- // Reactivatable for unlimited reuse
- // Works well on liquids, foils and in metal shopping carts
- // Robust construction provides optimal merchandise protection

### Product Codes

ZLDR9K1

### Technology

AM

### Environmental Constraints

#### Temperature

Maximum storage temperature not to exceed 50°C (122°F) for 96 hours at 80% RH.

#### Humidity

Unaffected by 80% humidity at 50°C (122°F), up to 96 hours.

#### Shelf Life

One year from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 30-80%.

### Product Compatibility

Sensormatic AM detection and deactivation devices.

### Mode of Application

Automatic

### Materials of Construction

#### Plastic Substrate

Polystyrene/Polyethylene 0.3mm (0.012in) thickness

#### Magnetic Acoustic Resonator

Resonant magnetic material. Amorphous alloy based on iron, containing nickel, cobalt, boron, and silicon

### Laminate

Low Density Polyethylene/Polyester  
0.119mm (0.0047in)

### Bias

Proprietary semi-hard magnetic material containing iron, nickel and chromium

### Adhesive

Double-coated, rubber-based adhesive:

// 2.4 mil thick each side

// Minimum peel strength of 2.27kg/5lbs

### Release Liner

Double-sided, silicon-coated liner:  
2 mil polyester

### Dimensions

**Color** ..... White

**Length**..... 44.6mm ± 0.15mm  
(1.76in ± 0.006in)

**Width** ..... 10.16mm ± 0.15mm  
(0.4in ± 0.006in)

### Label Thickness

(excluding liner)..... 1.20mm ± 0.13mm  
(0.047in ± 0.005in)

**Liner Width** ..... 48.64mm ± 0.75mm  
(1.915in ± 0.030in)

**Label Repeat** ..... 14.73mm ± 0.75mm  
(0.58in ± 0.03in)

**Label to Liner Spacing** ..... 2.02mm ± 0.75mm

**Note:** Warranty terms and conditions are as specified in the applicable Sales Agreement.

**CE** The acousto-magnetic (AM) label is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

See [Sensormatic.com](http://Sensormatic.com) for Usage Instructions

**Additional Consideration:**  
Must be applied to a rigid substrate

ROLL SPECIFICATIONS			
	Roll		Roll
PRODUCT CODE	ZLDR9K1	PRODUCT CODE	ZLDR9K1
Diameter Of Core	152.4mm (6in) core*	External Carton Dimensions	N/A
Max Roll Diameter	508mm (20in)	External Cubic Ft. Per Case	2.4
Number Splices	6 splices, 1 leader splice	Rolls Per Case	4
Roll Weight	4.09kg (9.02lbs)	Cases Per Pallet	16
Case Weight	18.87kg (41.60lbs)	Order Multiple	9,000-unit roll

\*Includes 3in core adapter