Sensormatic[®] | AM/RFID Hard Tag



AM/RFID Hard Tag

This hard tag features a highly sensitive Radio Frequency Identification (RFID) inlay for item-level visibility and inventory management and an AM EAS element for asset protection. The RFID component stores information specific to the protected merchandise for item-level and near real-time merchandise visibility. Source Tagging is available so retailers can receive floor-ready merchandise with consistent tag placement—expediting receiving and selling floor fulfillment. **Retailer Values**

- // Enables near real-time merchandise
 visibility
- // RFID element offers an efficient way to track inventory, while the AM EAS element provides product protection
- // Tagging at the point of manufacturing (Source Tagging) helps improve tag compliance and ensures consistent application
- // Source Tagged merchandise arrives floor-ready, enabling faster speed to sales floor

Solution Application

General Merchandise, Department Store, Specialty Apparel

Product Codes

New Dual Tag: IDTM2200 Re-Circulated Dual Tag: IDTM2200R In-Store Use: IDTM2200N Tack: MJ211B

Product Compatibility

Detachers AM/RFID Detachers: IDKM1000 IDKM1010

For AM Detaching Only: AMK1000 AMK1010

For AM Hand-Held Detaching Only: AMD3040

Detacher Type

SuperTag

Environmental Constraints Temperature

Maximum storage temperature not to exceed 60°C (140°F) for 96 hours at 80% RH.

Humidity

Unaffected by 80% humidity at 60°C (140°F), up to 96 hours

Materials of Construction

Tag Housing High-Impact ABS

Label Housing Low Density Polyethylene/Polyester/ Polyethylene 0.127mm (0.0050in)

RFID inlay Copper, Mylar, Silicon

Tack ABS Tack Head/Stainless-Steel Pin

Specifications

Specifications		
Color	Charcoal Gray	,
Length.		61mm (2.4in)
Width		30.5mm (1.20in)
Depth		24.6mm (0.97in)
Weight		8.8g (0.31oz)
Pullout	Force	36.29kg (80lbs)
EPC Me	mory 9	6 bits up to 128 bits
Operating Frequencies 860-960MHz		
Order m	nultiple	Tag: 1,000 Tack: 1,000
Carton \	-	g: 8.48kg (18.72lbs) ack: 1.17kg (2.57lbs)
Ext. Carton Dims.		
	Tag	: 476 x 292 x 219mm
	-	(18.75 x 11.5 x 8.6in)

Tag: 476 x 292 x 219mm (18.75 x 11.5 x 8.6in) Tack: 140 x 75 x 75mm (5.5 x 3 x 3in)

Ext. Carton Vol..... Tag: 0.031m³ (1.07ft³) Tack: 0.0008m³ (0.028ft³)

Cartons Per Pallet Tag: Atlanta DC: 32 Echt DC: 48

C C This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

* Visit sensormatic.com to download usage guidelines



© 2014 Tyco Retail Solutions. All rights reserved. TYCO RETAIL SOLUTIONS and SENSORMATIC are marks and/or registered marks. Unauthorized use is strictly prohibited.